



# INTERCOOL® *Glycol Fluids*

Product Information Bulletin

## ***INTERCOOL® OP-100***

***INTERCOOL® OP-100*** is chemically engineered using organic and inorganic inhibitors for corrosion protection in an *ethylene glycol* base and used as an Industrial Heat Transfer Fluid. The chemistry employed will effectively protect your industrial equipment whether constructed of single or mixed alloys. The industrial corrosion control inhibitors included have been specially formulated to extend the service life of the coolant. Therefore, you will receive a higher level of reserve alkalinity, superior performance, and less maintenance requirements through reinhibiting. These attributes improve your bottom line cost.

***INTERCOOL® OP-101*** is added initially and for remediation purposes when required. ***INTERCOOL®*** inhibitors, when added to *ethylene glycol* in the prescribed amount will protect such metals as Brass, Copper, Copper alloys, Steel, Cast Iron. ***INTERCOOL®*** inhibitors have successfully completed the 336-hour ASTM D-1384 corrosion test. A certificate of assurance is available upon request. Silicates are not used for corrosion protection in ***INTERCOOL®*** OP-100 or any other ***INTERCOOL®*** product.

***INTERCOOL® OP-100*** can be purchased in its concentrated form or preblended with deionized water to meet your specification for boiling, freeze and / or burst protection.



**INTERSTATE CHEMICAL CO., INC.**

2797 Freedland Road, Hermitage, PA 16148

FAX 724-981-8383 Phone 724-981-3771

